

QuoteID: 253949 Date: 2/28/2012 Customer PO:

Fab Status: PRODUCTION 31372 **Customer Number:** Req Ship Date:

Account/Billing Information: L T H STEEL STRUCTURES ** **LARRY HARVEY 1184 COUNTY LINE ROAD CUMMING, GA 30040-5410**

Email: LTHSTEELBUILDING@BELLSOUTH.NET Phone: (770) 781-8279 Fax: (678) 208-5613

Alternate Contact Information:

Project Name:

Shipping Information: NORTON, VA 24273 County: Norton

End User Information:

Engineering Design Info:

Building Type: Gabled Building

Width: 50' Length: 100' Height: 18' Slope: 3:12
Sidewall Bay Config: 4 bays at 25 ft

Left Endwall: Non-expandable Bearing Frame LEW Column Spacing: 15 / 20 / 15 Right Endwall: Non-expandable Bearing Frame REW Column Spacing: 15 / 20 / 15

LEW Girt: Flush REW Girt: Flush FSW Girt: Bypass BSW Girt: Bypass

Column Shape: Tapered

Code: IBC 2009 Wind Load: 95 Exposure: C

Live Load: 20 Reducible: Yes Ground Snow: 20 Roof Snow: 14 Seismic: Ss = 0.375 S1 = 0.121 Seismic Coefficient: 0.56 Collateral Load: 1 Snow Factors: Is = 1.0 Ct = 1.0 Ce = 1.0

Occupancy = Normal Thermal Conditions = Normally Heated/All Others Snow Exposure = All Other Roof/Terrain Conditions

Roof Dead Load = 2 psf

Building Colors:

Wall: Rustic Red (26 Gauge PBR) Roof: Galvalume Plus (26 Gauge PBR)

Eave Trim: Rustic Red

Downspout: Rustic Red Corner Trim: Rustic Red Jamb/Header Trim: Rustic Red

Doors & Factory Located Framed Opening Summary:

Size: 14X16 Wall: Left Endwall Bay: B Align: Center

Door Manufacturer <u>Model</u> Color **Insulated**

5250 **Rustic Red** Windloaded

Operator: Chainhoist Lock Option: Inside

Building Accessories:

DescriptionSelectedGutters and DownspoutsYesFramed Opening Jamb FlashingNoBase ClosuresYes

Standard Base Angle

Roof Extensions:

----No Roof Extensions Selected----

Liner Panel:

----No Liner Panel Selected----

Other Accessories:

 Description
 Qty
 Color

 H.S. Window
 *6030-I (6ft X 3ft)
 1
 Bronze

Option: Self-Flashing Window(s)

Doors Type M 3070 (Non-Windrated) (3ft X 7ft) 1 White

Swing Option: Left Handed

Option: Insulated

Lock Option: Standard Duty Knob Lock

Misc Framed Openings:

----No Misc Framed Openings Selected-----

Insulation:

DescriptionThicknessLocationSq FeetWhite Polypropylene (WMP-VR-R)6"Walls6306White Polypropylene (WMP-VR-R)4"Roof5523

Includes double sided tape and 2 roll(s) of patch tape.

Wall Fastener Type: **Standard** Length: **2"**Roof Fastener Type: **Long Life** Length: **2"**

Total Price Summary:

Base Building Price:

Building Freight:

Framed Opening Add:

Total Door Price:

DBCI Crating Charge:

Total Accessories Price (including fasteners, accessories):

Insulation Price: Insulation Freight:

Stamped with Design Calculations Overnight Service

Tax: To Be Added

Total Price (FOB seller's facility with freight allowed):

Estimated Weight:	26654 lbs
TERMS OF PAYMENT: 30% DEPOSIT FOR ENGINEERING, FABRICATION AND DELIVERY. BALANCE TO BE PAID BY CERTIFIED BANK CASHIERS CHECK ON DELIVERY.	
ACCEPTANCE OF ORDER	DATE
This quote is still current. The price is subject to change at anytime without notice. To lock this price buy now. Note: If a price increase occurs, this quote will need to be re-priced.	

Notes:

- Foundation: Anchor bolts by others
- Unless otherwise noted, the following specifications and conditions apply:
- All paneling incorporates the purlin-bearing profile
- Price includes long-life roof fasteners (lifetime red-rust warranty)
- The pre-punched connecting clips for the structural elements, including endwall columns, are welded in place and then primed during fabrication
- Buildings are engineered to meet listed codes and loads with the specified factory-located framed openings (size, location, and materials taken into account)
- All structural elements for the specified framed openings (girts, jambs, and headers) are pre-cut and prepunched and the necessary clips are welded on during fabrication
- Whenever possible, paneling is pre-cut to accommodate the specified factory-located openings (some panels may require cutting in the field)

Design Disclosures:

Soil Profile

Jobsite soil properties meeting the requirements of a Stiff Soil Profile have been assumed in the determination of Seismic design values. If you have questions concerning the particular conditions at your jobsite, this information should be verified by your Foundation Engineer or local Building Permit authority.

Enclosure

You have ordered this building to be designed as an enclosed structure. This means that all exterior components, including those not supplied by the manufacturer, MUST be designed for full wind load. This will require the installation of walk doors, roll-up and overhead doors, and windows rated to the wind expressed on the metal building drawings. Furthermore, these items must be installed in strict accordance with the manufacturer's instructions.

It is also possible that exterior components of the building, such as all doors and windows, must be constructed using projectile resistant materials. Consult your local building department for more information. Failure to comply with these requirements may create a situation endangering the lives of the inhabitants, or resulting in property damage. THE MANUFACTURER OF THE METAL BUILDING SYSTEM CANNOT BE HELD RESPONSIBLE FOR THIS IN ANY WAY.

This quote is still current. The price is subject to change at anytime without notice.

To lock this price buy now.

Note: If a price increase occurs, this quote will need to be re-priced.